

SLT-MOBITEL DIGITAL LIFESTYLE SOLUTIONS





SLT-MOBITEL FIBER

INTRODUCING SRI LANKA'S FASTEST INTERNET WITH UNRIVALED SPEEDS UP TO 100/1000Mbps. NOW YOU CAN CONNECT TO A TRULY LUXURIOUS LIFE AND ITS EVERY POSSIBILITIES FASTER THAN EVER BEFORE. SLT-MOBITEL PREMIUM FIBER CONNECTIVITY ENABLES YOU TO EXPERIENCE ULTRA HIGH SPEEDS WITH CRYSTAL-CLEAR VOICE & HD QUALITY PEO TV FACILITIES, ALONG WITH AN ARRAY OF SLT-MOBITEL SMARTHOME SOLUTIONS TO CREATE A LIFE OF CONVENIENCE. SAFETY AND TOTAL CONTROL.





SLT-MOBITEL SMARTHOME APP

THE FUTURE OF SMARTHOME
IS FAST APPROACHING &
IS RIGHT AT YOUR FINGER TIPS WITH
SLT-MOBITEL SMARTHOME.



SLT-MOBITEL SMARTHOME APP







EACH OF THESE FEATURES ARE COMPATIBLE WITH SLT-MOBITEL SMARTHOME, ENSURING A SEAMLESS USER EXPERIENCE FOR YOU.

POWER SAVING

REMOTE CONTROLLED

ALEXA COMPATIBLE

END TO END SERVICE

WITH SLT-MOBITEL SMARTHOME TECHNOLOGIES, YOUR HOME IS NOT ONLY SMART BUT ALSO MORE PRACTICAL THAN EVER BEFORE, WITH COMPLETE END TO END SERVICE OFFERED BY SLT-MOBITEL.

CORE PLATFORM

State-of-the-art SLT-MOBITEL SMARTHOME core platform is hosted securely in our tier-3 certified data centre with high availability and redundancy.

TAILOR-MADE TO SUIT YOUR DIGITAL LIFESTYLE

Select the best configuration that suits best for you from the latest devices available.

MANAGED SERVICE

SLT-MOBITEL takes care of the service delivery from the inception to post sales support up to maintenance. Installation of all your devices will be done by qualified professionals. You can get the assistance of 24x7 SLT-MOBITEL contact centre.

MULTI-MODAL ACCESS

You can control and manage your home via a mobile app, web portal and an on-premise controller. It also connects easily to voice command facilities with alexa and provides multi-user facility, giving control to your whole family.

COMMUNICATION MODE:



THE BENEFITS

- THE VOICE COMMAND FACILITY WITH ALEXA.
- INSTALLATION BY PROFESSIONALS.
- 24X7 CALL CENTRE SUPPORT.
- MULTI-USER FACILITY.

 (CAN BE OPERATED BY FAMILY MEMBERS)
- EASY PAYMENT SCHEME.



SCENE CONTROL

Say goodbye to the days of controlling one space with multiple switches. Customise multi-scene modes with just one touch and enjoy designing your day to complement your lifestyle.



LINKAGE CONTROL

Create your own personal Smart Home system, choose a target device and connect it with Smart Home devices creating a linkage relationship. That serves your needs best.



TIMING CONTROL

Delight in a space that is truly your own – convenient process that intuitively recognise individual behaviour and provide you with the option of setting up a variety of timed-functions.



REMOTE CONTROL

Enjoy absolute peace of mind when you're out of home. Take control of your space by connecting all your appliances to your mobile device with SLT-MOBITEL SMARTHOME App.

SLT-MOBITEL SMART HOME PACKAGE



HOME GATEWAY

Connect all your smart home hardware with the home gateway. You can easily access and use the smart home solutions through the app.



TWO GANG SWITCH

02 No.s

The best smart home solution to suite your life style.







SMART MOBILE SOCKET

02 No.s

Design a custom Smart Home solution, starting with a Home Gateway device at Rs. 27.450/-



SMART LIGHTING & POWER CONTROL

LIGHTING HAS A SUBSTANTIAL INFLUENCE ON OUR WELL-BEING AND
EVEN OUR HEALTH. THE SMART LIGHTING CONTROL FROM SLT-MOBITEL SMARTHOME
LETS YOU CONFIGURE THE BEST AMBIANCE IN LIGHT IN YOUR OWN HOME WITH EASE,
FLEXIBILITY AND MAXIMUM CONVENIENCE WHILE SAVING ENERGY AND MONEY.

SMART LIGHTING



WIRELESS SMART DIMMER SWITCH



SMART SWITCH (CIRCUIT BREAKER)



SMART SCENE SWITCH (6 BUTTONS)

WIRELESS SMART DIMMER SWITCH SMART SWITCH (CIRCUIT BREAKER) **SMART SCENE SWITCH (6 BUTTONS)**

COMMUNICATION MODE:



FFATURES

1. It can link with smart sensor to realise people come lights on.

2. Support time setting.

3. Scene editing, regional management, customise return-home and leave-home mode by a press.

PARAMETERS

Communication Protocol: IEEE 802.15.4 ZigBee/SmartRoom

Power Parameter: 110-240V AC. 50/60Hz

Minimum Load: 25W Maximum Load Impedance: 300W

(Incandescent Lamp/Halogen Lamp)

Material & Colour: White Flame Retardant Rating: UL94 V-0

Operating Temperature/Humidity:

-10°C - +45°C/95%RH (non condensing)

FFATURES

1. Maxim power detection chip: more accurate and sensitive in detection of high power electrical appliance.

2. Peak hour power detection, saving energy and create green living style. 3. User-friendly operation like time setting, scene management,

to maximally manage power use.

4. Energy statistics management to get real-time feedback of power consumption.

5. Users can turn off family power consumption remotely via App.

6. Can be centrally managed by energy control system to apply into distributed and centered property and home management system like apartments, hotels, office or commercials.

PARAMETERS

Power Parameter: 100-240V AC, 50/60Hz

Standby Power Consumption: 0.5W Rated Current: 32A

Installation Method: Guide Rail

Working Temperature/Humidity: -10°~+45°/ ≤95%RH

(non condensing)

FEATURES

1. Communication Mode: IEEE 802.15.4 (ZigBee/Smart Room).

2. It can be used with pre-setting scene on the App as a remote controller.

So user can switch defferent customised scenes without phone. It is operated easily to take care of

family members.

3. It can bind with several devices (Smart Switch, Smart Rainbow Bulb. Smart Curtain Motor) to realise real-time control.

PARAMETERS

Power Parameter: DC3V

Working Temperature/Humidity:

CR2450*2, Button Battery

Bandwidth: 2.405~2.480GHz

Communication Distance: 100m (depend on specific

environmental conditions)

Installation Method: Wall-mounted Type, Portable Type

> -10°~+45°/≤95%RH (non condensing)

PG 9 | SLT-MOBITEL SMARTHOME

SMART POWER CONTROL







SMART METALLIC SWITCH
(ONE GANG)

SMART METALLIC SWITCH (TWO GANGS)

SMART METALLIC SWITCH (THREE GANGS)

SMART METALLIC SWITCH (ONE GANG)

SMART METALLIC SWITCH (TWO GANGS)

SMART METALLIC SWITCH (THREE GANGS)

FEATURES

1. Support time setting.

2. Scene editing, regional management, customize return-home and leave-home

made by a press.

3. Unique live line technology,

easy wiring and bring peace of mind.

4. Elegant design.

5. No need to change your existing wiring & sun box.

6. Metalic finish.

7. Push button.

8. Light indicator / active status.

PARAMETERS

Power Parameter: 100-240V AC, 50/60H z

Total Maximum Resistance Load: 100V~: Max.1000W/10A

Incandescent Lamp: 240V~: Max.2400W/10A

Total Maximum Inductive/Capacitive Load: 100V~:Max650W/6.5A

Energy Saving Lamp/Fluorescent Lamp/LED: 240v~: Max 1560W/6.5A

Installation Method: Wall-mounted Type

Working Temperature/Humidity: -10° ~+45°/ \leq 95%RH

(non condensing)

Material & Colour: PC + Aviation aluminium (Metalic – Silver)



POWER SAVING



REMOTE CONTROLLED



ALEXA COMPATIBLE

SMART POWER CONTROL



SMART TOUCH SWITCH (ONE GANG, L)



SMART TOUCH SWITCH (TWO GANGS, L)



SMART TOUCH SWITCH (THREE GANGS, L)

SMART TOUCH SWITCH (ONE GANGS, L)

SMART TOUCH SWITCH (TWO GANGS, L)

SMART TOUCH SWITCH (THREE GANGS, L)

COMMUNICATION MODE:



FEATURES

1. Communication Mode: ZigBee
2. Convenient and energy saving
3. Compatible with existing electrical wiring
4. With capacitive touch technology
(Tempered glass), it is safer to operate
through glass even by wet hand,
which is suitable for the bathroom,
laundry room, kitchen

PARAMETERS

Power Parameter: 100-240V AC, 50/60H z

Total Maximum Resistance Load: 100V~: Max.1000W/10A

Incandescent Lamp: 240V~: Max.2400W/10A

Total Maximum Inductive/Capacitive Load: 100V~:Max650W/6.5A

Energy Saving Lamp/Fluorescent Lamp/LED: 240v~: Max 1560W/6.5A

Installation Method: Wall embedded inside standard sun box


Working Temperature/Humidity: -10°~+45°/≤95%RH (non condensing)

Material & Colour: Tempering Glass White





POWER SAVING



Net Weight: 152g Gross Weight: 317g



REMOTE CONTROLLED



ALEXA COMPATIBLE

SMART POWER CONTROL

WIRELESS SMART SOCKET (UK STANDARD, L&N)

SMART MOBILE SOCKET (Metering type)



WIRELESS SMART SOCKET
(UK STANDARD, L&N)



SMART MOBILE SOCKET (METERING TYPE)

FEATURES

1. Plug and Play, UK standard.
2. Pre schedule your daily tasks & control the devices via smart home App.
3. Timing the smart socket to supply power or cut off power at certain time to realize smart control on home appliance.
4. Overload protection, safe for use.

PARAMETERS Power Parameter: 250V AC, 50/60Hz

Rated Current: 13A

Maximum Resistance Load: 2500W

Maximum Inductive & Capacitive Load: 1500W

Installation Method: Wall-mounted Type

Working Temperature/Humidity: -10°~+45°/ ≤95%RH (non condensing)

Material & Colour: PC, White

FEATURES

Conform to the UK standard; support remote controlling
 the socket power.

2. Metering type, get real-time data of power consumption.

Manage the electricity by time setting, linkage control and peak-power limitation, saving your time.

4. Overload protection, safe for use.

PARAMETERS

Power Parameter: 250V AC, 50/60Hz

Maximum Rated Current: 13A
Standby Power Consumption: ≤0.5W
Maximum Resistance Load: 2500W

Maximum Inductive & Capacitive Load: 1500W

Working Temperature/Humidity: -10°~+45°/ ≤95%RH (non condensing)



SMART HOME SENSORS

AN INTELLIGENT HOME ALWAYS KEEPS YOU IN THE KNOW.

STAY INFORMED IN CONTROL OF EVERYTHING HAPPENING IN AND

AROUND YOUR HOME - WHETHER YOU'RE IN THE KITCHEN OR

ACROSS THE WORLD.

SMART SENSORS



WIRELESS IR TRANSMITTER (FULL DIRECTION)



WIRELESS IR TRANSMITTER (TOP EMITTED)



WIRELESS IR TRANSMITTER (SIDE EMITTED)

WIRELESS IR TRANSMITTER (FULL DIRECTION)

WIRELESS IR TRANSMITTER (TOP EMITTED)

SMART SCENE SWITCH (SIDE EMITTED)

FEATURES

- 1. Remotely control all smart home appliances
- 2. High responsive signal emitter covering 360°
- 3. Can use with your other smart devices to build schedule/scene management/linkage control

PARAMETERS

Power Parameter: 100-240V AC, 50-60Hz

Control Distance: 5m

Control Angle: 360° (Full Direction)

Ceiling-mounted Type,

Installation Method: Wall-hanging Type

Working Temperature/Humidity: -10°~+45°/ ≤95%RH

(non condensing)

FEATURES

1. Remotely control all smart home appliances

2. Can use with your other smart devices to build schedule/scene management/linkage control

PARAMETERS

Power Parameter: DC 3V, CR2 batterv*1

Control Distance: 5m

Control Angle: 45°

Installation Method: Portable Type, Base-fixed

Working Temperature/Humidity:

-10°~+50°/ ≤95%RH (non condensing)

FEATURES

1. Remotely control all smart home appliances 2. Can use with your other smart devices to build schedule/scene management/linkage control

PARAMETERS

Power Parameter: DC 3V, CR2 battery*1

Control Distance: 5m

Control Angle: 45°

Installation Method: Portable Type, Base-fixed

Working Temperature/Humidity: -10°~+50°/ ≤95%RH

(non condensing)

SMART SENSORS







SMARTROOM CONTACT SENSOR

WIRELESS MULTI-FUNCTIONAL DETECTOR

SMART GAS DETECTOR

SMARTROOM CONTACT SENSOR
WIRELESS MULTI-FUNCTIONAL
DETECTOR
SMART GAS DETECTOR

COMMUNICATION MODE:



FEATURES

- 1. Communication Mode: IEEE 802.15.4 (ZigBee/Smart Room).
- As a security device, once it is opened illegally, pre-set alarm devices will be triggered, and send alarm message to phone.
- As a trigger device, it can be linked to turn on the lights,
 play background music and so on.
- Remote monitor the opening/closing state of door/window.
 Low power consumption, energy saving.

PARAMETERS

Power Parameter: DC3V

Battery Type: CR2 battery*1

Alarm Distance: 20 (mm)

Installation Method: Fixed by screws

Working Temperature/Humidity: -10°~+45°/ ≤95%RH

(non condensing)

FEATURES

- As a motion detector, it can be linked to turn on the lights,
 play background music and so on/sense environmental
 temperature change/detect light intensity.
- 2. Combine with other security devices and alert the user.
 - Low power consumption, energy saving.
- Strong anti-interference ability, stable detection signal
 Accurate motion detection capability.
- 6. Installation method : Base fix (include this as the 4th point)

PARAMETERS

Power Parameter: DC3V

Battery Type: CR2 battery*1

Detection Angle: Circumference with a Radius of 3m

when the Height is 2.4m

Installation Height: 2.3 -6 m

Working Temperature/Humidity: -10°~+45°/≤95%RH

(non condensing)

FEATURES

- 1. Communication Mode: IEEE 802.15.4 (ZigBee/Smart Room).
- It can realize linkage alarm with other devices to detect gas leakage.
 3. Send alarm information in time.
- 4. Reliable operation, stable performance and low false alarm rate.

PARAMETERS

Power Parameter: 100-240V AC, 50/60Hz

Alarm Decibel: >80dB@lm
Alarm Concentration: 9%LEL±1%

Detecting Gas type: Natural Gas, Liquefied Gas

Detection Mode: Catalyst Contact Combustion

Type Sensor

 ${\bf Communication\ Distance:}\quad {\bf 300m\ (depend\ on\ specific}$

environmental conditions)

Installation Method: Side wall Type. Ceiling Type
Working Temperature/Humidity: -10°C~+45°C ≤95%RH

(non condensing)

PG 15 I SLTMOBITEL SMARTHOME

SMART SENSORS





SMART TEMPERATURE AND HUMIDITY SENSOR

WIRELESS SMOKE DETECTOR

SMART TEMPERATURE AND HUMIDITY SENSOR
WIRELESS SMOKE DETECTOR

COMMUNICATION MODE:



FEATURES

1. Communication Mode: IEEE 802.15.4 (ZigBee/SmartRoom)

2. It can detect temperature & humidity and send the data to App by ZigBee protocol.

So that user can control linked devices remotely to keep the indoor environment healthy.

When the voltage of battery is too low, mobile terminals will receive under voltage alarm to remind user of replacing battery.

4. Low power consumption, energy saving.

5. Wireless design, small size, easy to install.

6. Stylish and exquisite design.

PARAMETERS

Power Parameter: DC 3V, CR2*1

Standby Current: <2µA

Detection Power Consumption: <10mA

Communication Distance: 100m (depend on specific

environmental conditions)

60°C~70°C/±1°C)

FEATURES

1. Communication Mode: IEEE 802.15.4 (ZigBee/Smart Room).

2. It can apply to ZigBee Smart Security System.

Push notifications can be seen on App.

3. Work with Smart Sound warner for

local alarm while sending messages via App.

4. Support tamper alarm.

5. Strong anti-interference ability with low false alarm rate.

PARAMETERS

Power Parameter: DC3V

Battery Type: CR2 battery*1

Alarm Decibel: 70dB, 1m

Installation Method: Base-fixed

Working Temperature/Humidity: -10°~+45°/ ≤95%RH (non condensing)



SMART SECURITY

HOME SECURITY IS MUCH MORE THAN DOOR CONTACTS AND ALARMS.

AT SMART SECURITY SOLUTIONS, WE OFFER THE LATEST SMART HOME
FEATURES SUCH AS VOICE COMMANDS/LIVE & RECORDED VIDEO FEEDS,
LIGHT AUTOMATIONS AND SO MUCH MORE.

SMART SECURITY



WIRELESS SMART LOCK
(FINGERPRINT & PASSWORD)

WIRELESS SMART LOCK
(FINGERPRINT & PASSWORD)

WIRELESS PANIC (EMERGENCY) BUTTON

COMMUNICATION MODE:



FFATURES

Support multiple access methods: Remote methods/ smart phone/ local method such as passwords/keys: user scan set double safe protection, (door open with both fingerprint and password)
 2. Restrict and notify illegal access.

 3. Ultra-low power consumption, long endurance
 4. Traditional key unlocking way available

 5. Support multiple users up to 350 and real time alerting.

6. Access lock

PARAMETERS

Power Parameter: DC 9V

Battery Type: 8 AA Battery (4 for backup)

Number of fingerprint: 60 user* 5 fingerprint

Working Temperature/Humidity: -20°~+50°/ ≤95%RH

(non condensing)



SMART SECURITY



WIRELESS PANIC
(EMERGENCY) BUTTON

WIRELESS PANIC (EMERGENCY) BUTTON

COMMUNICATION MODE:



FEATURES

- 1. Communication Mode: IEEE 802.15.4 (ZigBee/Smart Room).
- 2. Support emergency alarm and remote push notification.
 - 3. Small size, no wiring, portable.

PARAMETERS

Power Parameter: DC 3V, CR2450*1

Installation Method: Wall-hanging Type, Portable Type
Working Temperature/Humidity: -10°-+45°/ <95%RH (non condensing)

SMART ACCESS





WIRELESS DOOR BELL BUTTON

WIRELESS DOOR BELL

WIRELESS SMART LOCK (FINGERPRINT & PASSWORD)

WIRELESS PANIC (EMERGENCY) BUTTON

COMMUNICATION MODE:



FEATURES

1. Small size, no wiring, portable.

2. Low power consumption, energy saving.

3. Real time alerts.

4. Solid and durable.

PARAMETERS

Power Parameter: DC 3V, CR2450*1

Working Temperature/Humidity: -10°~+45°/≤95%RH (non condensing)

FEATURES

1. Used with doorbell button; Get prompts on phone.

2. Can link with door lock and door bell.

3. Easy to install and operate.

4. A variety of ringtones to select.

PARAMETERS

Power Parameter: 100-240V AC, 50/60 Hz

Alarm Decibel: Adjustable



SMART CURTAIN SOLUTIONS

MOTORISED CURTAIN CAN BE OPENED AND CLOSED SIMPLY BY TOUCHING A BUTTON,
A REMOTE CONTROL, OR AN APP ON A SMARTPHONE. WINDOW COVERINGS ARE A PROVEN WAY TO
REDUCE SOLAR GAIN AND PREVENT HEAT LOSS, AND IF THEY ARE THIS EASY TO OPEN AND CLOSE,
IT'S MUCH MORE LIKELY YOU'LL REMEMBER TO DO SO TO BENEFIT YOU AND YOUR ENVIRONMENT.
ADDITIONALLY, THE ABILITY TO SET SCHEDULES TO OPEN AND CLOSE THEM AT SPECIFIC TIMES
MEANS YOU MAY NEVER HAVE TO WORRY ABOUT THEM AT ALL.

SMART CURTAIN SOLUTIONS







SMARTROOM CURTAIN MOTOR

SMARTROOM CURTAIN CONTROLLER

SMART METALLIC CURTAIN SWITCH

SMARTROOM CURTAIN MOTOR

SMARTROOM CURTAIN CONTROLLER

SMART METALLIC CURTAIN SWITCH

COMMUNICATION MODE:



FEATURES

 Open or close the curtain by a touch or press on the switch panel or via App,

2. Support time setting and linkage control to bring convenience.

3. Design of noiseless; Stop when facing with obstacles.
4. Manual operational capability

PARAMETERS

Power Parameter: 100-240AC 50/60Hz

Input Power: 80W

Load Capacity: 100Kg

Rotate Speed: 80rpm

Installation Method: Clamping Hold

Working Temperature/Humidity: -20° +65 $^{\circ}$ / \leq 95%RH

(non condensing)

FEATURES

Connect to existing AC powered curtain motor
 to take control.

2. Open or close the curtain by a touch or press on the switch panel or via App.

3. Support time setting and linkage control to bring convenience.

4. Wireless smart touch curtain controller

PARAMETERS

Power Parameter: 100-240V AC50/60Hz

Load Type: AC Curtain Motor

Motor Power: 125W, 50/60Hz

Installation Method: Wall-Embedded inside

standard sun box

Working Temperature/Humidity: -10° ~+45°/ \leq 95%RH

(non condensing)

FEATURES

1. Antenna Configuration: Internal Antenna.

2. Power Parameter: 100-240V AC,50/60HZ

3. Stand-by Power

4. Load Type: AC Curtain Motor.

5. Wireless smart touch curtain controller.

6. Motor power - 123 W, 50/60 Hz

PARAMETERS

Power Parameter: 100-240AC 50/60Hz

Load Type: AC Curtain Motor

Motor Power: 125W, 50/60Hz

Installation Method: Wall-Embedded inside

standard sun box

Working Temperature/Humidity: -10°~+45°/ ≤95%RH

(non condensing)

Material & Colour: Metallic, Sliver/Champagne gold

PG 22 | SLT-MOBITEL SMARTHOME

SMART CURTAIN SOLUTIONS



SMART HOME CURTAIN TRACK

SMART HOME CURTAIN TRACK

COMMUNICATION MODE:



FEATURES

Communication Mode: IEEE 802.15.4
 (ZigBee/SmartRoom).

2. Open or close the curtain by a touch or press on

the switch panel or via App, free your hand.

3. Support time setting and linkage control to bring convenience.

4. Design of noiseless; Stop when facing with obstacles.

5. Keep the traditional operation method.

PARAMETERS

Power Parameter: 100-240V AC50/60Hz

Standby current: ≤0.1W

Input Power: 80W

Load Capacity: 100 kg

Working Temperature/Humidity: 80 RPM

Rotate Speed: 0.34A

Rated Current: Clamping Hold

Installation Method: -20°C~+45°C/ ≤95%RH (non condensing)

Material and Colour: PC, Grey

Dimensions (L*W*H): 310*68*50 (mm)

CCTV SOLUTIONS

CCTV CAMERA SURVEILLANCE
OFFERS YOU THE ABILITY TO
REMOTELY MONITOR YOUR HOME
AND ALSO PROVIDE A SEAMLESS
STORAGE SOLUTION THAT SAVES
SECURITY FOOTAGE ON
SLT-MOBITEL AKAZA CLOUD.
YOU CAN NOW LEAVE YOUR
HOUSE WITH PEACE OF MIND AND
CHECK-IN AT ANY TIME THAT YOU
ARE AWAY FROM HOME.



- Convenience of paying via credit card or adding it to your monthly SLT-MOBITEL Bill
- Selection of a preferred camera package and number of days to save recordings on cloud storage

FEATURES

- · High quality cameras with multiple packages
- Offer as a managed service by SLT-MOBITEL including after sales technical support and maintenance
 - · Remote access via APP & web
- · Access past recordings for 7 days from anywhere and anytime.

BROADBAND DATA CONSUMED FOR
VIDEO STREAMING IS FREE FOR
SLT-MOBITEL BROADBAND CUSTOMER

- 1-3 CAMS
 Monthly charge
 Rs.399
- 4 CAMS
 Monthly charge
 Rs.599

8 CAMS
Monthly charge
RS.999

16 CAMS
Monthly charge
Rs.1999



EAZY STORAGE

POWERED BY SLT-MOBITEL AKAZA CLOUD, EAZY STORAGE IS THE PERFECT SOLUTION FOR ALL YOUR STORAGE NEEDS ONLINE.
SAVE ALL YOUR IMPORTANT MESSAGES, VIDEOS, PHOTOS, MUSIC AND DOCUMENTS
CONVENIENTLY AND SECURELY.

OFFERINGS

- Edit, organise and store all your files
- Lowest storage cost in the market
- Ability to change privacy settings of individual files and enable sharing content with others or making specific content private
- Automatically sync files and folders to your desktop
- No more irritating online ads, popups and notifications
 - Efficient built in file search engine
 - Be safe from data infringers

Sign-up to the 5GB Experience package and enjoy a 60-day free trial.

Packages start from Rs. 50/-.
Storage space options of 5GB, 50GB, and 100GB and more to choose from.